

PERFORMANCE METAL POWDER-BED FUSION 3D PRINTING

XM200S



XACT METAL

THE XM200S IS A HIGH-PERFORMANCE METAL POWDER-BED FUSION PRINTER AT AN ACCESSIBLE PRICE

By taking the essential additive manufacturing specs for metal powder-bed fusion (commonly known as Selective Laser Melting or Direct Metal Laser Sintering) and combining them with cutting-edge technology, the XM200S is able to offer uncompromising quality for users.

The XM200S makes quality metal powder-bed fusion 3D printing available to customers in high-performing

applications like aerospace, medical and other applications where print speed is critical.

Metal powder-bed fusion provides high-quality and complex parts. It reduces total cycle time by about 50% and removes the need for wash/debinder and sintering/oven equipment used in bound metal deposition, atomic deposition additive manufacturing or other FDM-like metal 3D printers.

XM200S SPECIFICATIONS

- Large cubic build volume allows you to print multiple parts more efficiently and quickly.
- 200W Yb fiber laser provides optimal power density and prints 20-100 μm layers with a spot size greater than 50 microns, providing precision to your build.
- Precision high-speed scanner has minimal drift and warm-up time.
- Patent-pending recoater uses a unique “bulb” shape recoating element that spreads powder like a blade yet provides compaction similar to a rolling element. The recoater’s compliant design allows it to negotiate out-of-plane growth.
- Build chamber is easy to set up and simple to clean and maintain.
- Easy user access to filters, particle collection and overflow container.
- Inert swap housing provides quick and safe filter changeovers.
- Small footprint makes it easier to include additive manufacturing in your factory, lab or facility.
- Modern software architecture offers a streamlined, intuitive and functional platform that supports visual workflows and remote monitoring.
- Open platform provides qualified users the ability to develop their own printing parameters and use their own powder.

TECHNICAL DATA

Build Volume	125 in ³ (5 x 5 x 5 in) 2,048 cc (127 x 127 x 127 mm)
Exterior Dimensions	Approx. 37 x 24 x 67.5 in ³ - W x D x H (940 x 610 x 1,715 mm ³)
Laser Type	200W Yb fiber laser
Precision Optics	Spot size greater than 50 microns
Scanner	<ul style="list-style-type: none">• High-performance galvanometer scanner• Scan speed up to 8 m/s• 16-bit or greater command resolution
Electrical	<ul style="list-style-type: none">• Power Supply 200-240 VAC Single Phase, 50/60 Hz• Consumption 2,900W
User Interface	15" intuitive user-friendly touch screen
Weight	Approximately 400 lbs (181 kgs)
Powder Options	<ul style="list-style-type: none">• Aluminum Si10Mg• Bronze• Stainless Steel: 316L, 17-4 PH, 15-5, 400 Series• Super Alloys: 718, 625, Cobalt Chrome F75, Hastelloy[®] X• Titanium Ti64• Tooling Steels: Maraging M300, H13
Price	\$145,000 USD

Contact us at +1 (814) 205-1505 or info@xactmetal.com to learn more.

Xact Metal is a trademark of Xact Metal, Inc.

